

# HYGIENIC MULTI TUBE HEAT EXCHANGERS WITH REMOVABLE TUBES

### **HRS MR SERIES**



The HRS MR Series is a complete stainless steel shell and tube heat exchanger designed for hygienic applications. The product flows through both the inner tube and the surrounding shell for regeneration duties. The removable tubes allow hygienic processing on the shell side.

The MR Series is an ideal heat exchanger for direct product-to-product heat recovery. Using HRS corrugation technology, heat transfer and efficiency are increased over standard smooth tube heat exchangers. In addition, effects of fouling are minimised.



## TECHNICAL DATA

#### **APPLICATIONS**

Low-Medium Viscosity Fluids Food Industry Applications

#### STANDARD MATERIALS OF CONSTRUCTION

Service Side: AISI 316L Stainless Steel Product Side: AISI 316L Stainless Steel Other material options available

#### STANDARD CONNECTIONS

Service Side: Clamp Product Side: Clamp All clamp types available

#### SURFACE FINISH

External: Polished Internal: <0.8µ Other surface finishes available

#### STANDARD DESIGN CONDITIONS

Service Side:	10 bar/185°C
Product Side:	10 bar/185°C

#### FEATURES

- Corrugated tubes for increased heat transfer
- Multiple units can be interconnected and have the option of frame mounting, insulation and cladding in stainless steel

#### RANGE

MODELS	LENGTHS (m)	SURFACE AREA (m <sup>2</sup> )	SERVICE SIDE CONNECTION	PRODUCT SIDE CONNECTION	MAX FLOW SERVICE (m <sup>3</sup> /hr)	MAX FLOW PRODUCT (m³/hr)	SERVICE SIDE VOLUME (I)	PRODUCT SIDE VOLUME (I)
MR 7 76/18	3 - 6	2.3	2"	2.5"	16	13	14.4	8.3
MR 12 104/18	3 - 6	4	3"	4"	39	25	28.5	14.3
MR 19 129/18	3 - 6	6.3	3"	5"	39	39	44	22.6
MR 31 154/18	3 - 6	10.4	4"	6"	76	62	58.2	36.8

The surface area and volumes shown are for 6m length models.

#### DESIGN CODE AND COMPLIANCE

PD 5500, PED 2014/68/EU, ASME | FDA, TR CU 032, DOSH Compliant

HRS HEAT EXCHANGERS hrs-heatexchangers.com Malaysian Office +603 8081 1898 info@my.hrs-he.com